

# Bosch Professional Series: the first choice for Builders.

**55°C FACTORY SET UNIT NOW AVAILABLE**



The latest project range of Bosch continuous flow hot water systems has been specifically designed for superior quality, high energy efficiency and ease of installation for your building projects.

Whether building a new home, or replacing an existing hot water system as part of a renovation, a **Bosch Professional (21L/min)** or **Bosch Professional Plus (26L/min)** provides uncompromised quality while being compact, space-saving and easy to install.

#### Key Features:

- ▶ 50°C temperature limited models available - no need for additional tempering valves
- ▶ Professional Plus is also available as a temperature adjustable unit
- ▶ 5.5+ star energy efficiency rating
- ▶ Easy installation
- ▶ Compact design
- ▶ Install up to 4 optional temperature controllers
- ▶ Available in Natural or LP Gas
- ▶ Comprehensive warranties for domestic installations available

For more information call 1300 30 70 37 or visit [www.bosch-climate.com.au](http://www.bosch-climate.com.au)



# BOSCH

## Hot Water



## Security Bracket

### BLB70

Bosch offers a security bracket made from 2mm thick galvanised plate steel which attaches to the wall and the hot water system to secure your investment. Padlock is not included.

#### Dimensions

Height: 60mm  
Width: 175mm  
Depth: 35mm



## Project Recess Box

### PRB50L - Professional PRB26L - Professional Plus

Ideal for new homes, allows the Bosch Professional or Bosch Professional Plus to be completely recessed, saving space and protecting the appliance. The project recess box can also be painted to suit the appearance of the home.

#### Brick opening dimensions

Height: 930mm  
Width: 345 mm  
Depth: 145mm  
(minimum dimensions)



## Pipe Cover

### YPHC304

A pipe cover\* can be easily attached to the Bosch Professional or Bosch Professional Plus. It conceals the pipes leading to the appliance, giving a neat and smooth finish to the installation. This allows the power point to be sheltered beneath the cover.

\*Available for non-recessed models only

#### Dimensions

Height: 410mm  
Width: 342mm



**Bosch Professional**  
(21L/min)

**Bosch Professional Plus**  
(26L/min)

Specifications	Model		
	Bosch Professional	Bosch Professional Plus	Bosch Professional Plus 55°C factory set
<b>Part Number</b>	YS2170RA5P	YS2670RA5P	YS2670RAHP
<b>Installation</b>	External	External	External
<b>Ignition</b>	Electronic	Electronic	Electronic
<b>L/min (25°C rise)</b>	21	26	26
<b>Min. operating inlet water pressure (kPa)</b>	100	100	100
<b>Min. constant water pressure for Max flow (kPa)</b>	130	230	230
<b>Max. inlet water pressure (kPa)</b>	1000	1000	1000
<b>MJ/hr</b>	170	200	200
<b>Star Rating</b>	5.56	5.53	5.53
<b>Temperature</b>	50°C limited	50°C limited	Preset at 55°C
<b>Antifrost</b>	Standard	Standard	Standard
<b>Gas Type</b>	NG/LPG	NG/LPG	NG/LPG
<b>Electrical Supply</b>	230-240 VAC 50 Hz (10A weatherproof power point required within 500mm of the unit)		
<b>Temperature Controller</b>	Up to 4 temperature controllers can be installed (Premium Controllers: YPRM67XBN, YPRS67XBN: Sub controller: YPRP62XB)		
<b>Unit Height x Width x Depth (mm)</b>	520x350x170	600x350x170	600x350x170
<b>Carton Weight (kg)</b>	19	22	22
<b>Domestic Warranty</b>			
<b>Parts &amp; Labour</b>	3 Years	3 Years	3 Years
<b>Heat Exchanger (part only)</b>	10 Years	10 Years	10 Years
<b>Pipe Connection Sizes</b>			
<b>Natural Gas</b>	20mm (3/4")	20mm (3/4")	20mm (3/4")
<b>LP Gas</b>	20mm (3/4")	20mm (3/4")	20mm (3/4")
<b>Cold Water</b>	20mm (3/4")	20mm (3/4")	20mm (3/4")
<b>Hot Water</b>	20mm (3/4")	20mm (3/4")	20mm (3/4")

**Contact Us:** 1300 30 70 37 or visit [www.bosch-climate.com.au](http://www.bosch-climate.com.au)